c2156

INTERNATIONAL STANDARD

ISO 8613-6

First edition
1989-09-01

Information processing — Text and office systems — Office Document Architecture (ODA) and interchange format —

Part 6 :
Character content architectures

Traitement de l'information — Bureautique — Architecture des documents de bureau (ODA) et format d'échange —

Partie 6 : Architecture des contenus de caractères

Reference number
ISO 8613-6 : 1989 (E)

Contents

Page

Foreword vi

1 Scope 1

2 Normative references 2

3 Definitions 3

4 General principles 3
- **4.1** Classes 3
- **4.2** Content 3
- **4.3** Presentation attributes 3
- **4.4** Control functions 4
- **4.5** Graphic characters 4
- **4.6** Space characters 4
- **4.7** Coding of content information 4
- **4.8** Internal structure 5
  - **4.8.1** Formatted content 5
  - **4.8.2** Processable content 5
  - **4.8.3** Formatted processable content 5

5 Character positioning 6
- **5.1** Basic concepts 6
  - **5.1.1** Character fonts 6
  - **5.1.2** Directions 6
  - **5.1.3** Character image model 7
  - **5.1.4** Character spacing 8
  - **5.1.5** Active position 8
  - **5.1.6** Positioning area 9
  - **5.1.7** Line boxes 9
- **5.2** Positioning of character images within a line box 10
  - **5.2.1** Spacing between characters 11
  - **5.2.2** Alignment 12
  - **5.2.3** Tabulation 12
  - **5.2.4** Character ordering 13

© ISO 1989
All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

5237

5.2.5 Parallel annotation ... 13
5.2.6 Subscript/superscript ... 15
5.2.7 Pairwise kerning ... 15
5.2.8 First line offset ... 15
5.2.9 Itemization ... 15
5.3 Positioning of line boxes within a basic layout object ... 17

6 Character imaging ... 17
6.1 Emphasis ... 18
6.1.1 Weight ... 18
6.1.2 Posture ... 18
6.1.3 Underlining ... 19
6.1.4 Blinking ... 19
6.1.5 Image inversion ... 19
6.1.6 Crossing–out ... 19
6.2 Font selection ... 19
6.2.1 Font specification ... 20
6.2.2 Font designation ... 20
6.2.3 Font invocation ... 20
6.3 Subscript and superscript ... 20
6.4 Character combinations ... 21

7 Definition of character presentation attributes ... 21
7.1 Shared presentation attributes ... 22
7.1.1 Alignment ... 22
7.1.2 Character fonts ... 22
7.1.3 Character orientation ... 23
7.1.4 Character path ... 23
7.1.5 Character spacing ... 23
7.1.6 Code extension announcers ... 24
7.1.7 First line offset ... 24
7.1.8 Graphic character sets ... 24
7.1.9 Graphic character subrepertoire ... 25
7.1.10 Graphic rendition ... 25
7.1.11 Itemization ... 24
7.1.12 Kerning offset ... 26
7.1.13 Line layout table ... 27
7.1.14 Line progression ... 27
7.1.15 Line spacing ... 28
7.1.16 Pairwise kerning ... 28
7.2 Layout presentation attributes ... 28
7.2.1 Formatting indicator ... 28
7.2.2 Initial offset ... 29
7.3 Logical presentation attributes ... 30
7.3.1 Indentation ... 30
7.3.2 Orphan size ... 30
7.3.3 Proportional line spacing ... 30
7.3.4 Widow size ... 31
7.4 Content architecture class attributes ... 31
7.4.1 Content architecture class ... 31
7.4.2 Content type ... 31
7.5 Interactions between presentation attributes and layout directives ... 31

8 Character content portion attributes ... 32
8.1 Common coding attributes ... 32
8.2 Other coding attributes ... 32

9 Formal definitions of character content architecture dependent data types ... 32
9.1 Introduction ... 32
9.2 Representation of presentation attributes ... 33
9.3 Representation of coding attributes ... 35
9.4 Representation of non–basic features and non–standard defaults ... 35

10 Graphic characters 37

11 Definition of control functions and the character SPACE 37
11.1 Shared control functions 38
11.1.1 CR – Carriage Return 38
11.1.2 GCC – Graphic Character Composition 38
11.1.3 IGS – Identify Graphic Subrepertoire 39
11.1.4 LF – Line Feed 39
11.1.5 PLD – Partial Line Down 39
11.1.6 PLU – Partial Line Up 40
11.1.7 SCS – Set Character Spacing 40
11.1.8 SGR – Select Graphic Rendition 40
11.1.9 SHS – Select Character Spacing 41
11.1.10 SLS – Set Line Spacing 42
11.1.11 SRS – Start Reverse String 42
11.1.12 STAB – Selective Tabulation 42
11.1.13 SUB – Substitute Character 42
11.1.14 SVS – Select Line Spacing 42
11.1.15 VPB – Line Position Backward 43
11.1.16 VPR – Line Position Relative 43
11.1.17 Code extension control functions 43
11.2 Layout control functions 43
11.2.1 BS – Backspace 43
11.2.2 HPB – Character Position Backward 43
11.2.3 HPR – Character Position Relative 44
11.2.4 JFY – No Justify 44
11.2.5 SACS – Set Additional Character Spacing 44
11.2.6 SRCS – Set Reduced Character Spacing 44
11.2.7 SSW – Set SPACE Width 44
11.3 Logical control functions 45
11.3.1 BPH – Break Permitted Here 45
11.3.2 NBH – No Break Here 45
11.3.3 PTX – Parallel Texts 45
11.4 Delimiters 45
11.4.1 SOS – Start Of String 45
11.4.2 ST – String Terminator 45
11.5 SP – Space 45

12 Content layout process 46
12.1 Introduction 46
12.1.1 Purpose 46
12.1.2 Available area 46
12.1.3 Presentation attributes 46
12.1.4 Character content architecture classes 47
12.1.5 Use of delimiters 47
12.1.6 Layout of the content 47
12.1.7 Layout sequence 47
12.2 Content layout process for processable content 48
12.2.1 Single basic logical object to single basic layout object 48
12.2.2 Single basic logical object to multiple basic layout objects 52
12.2.3 Multiple basic logical objects to single basic layout object 52
12.3 Content layout process for formatted processable content 53
12.4 Content layout process for formatted content 53

13 Content imaging process 53
13.1 Introduction 53
13.2 Content imaging process for formatted content 54
13.2.1 Determination of initial point 54
13.2.2 Choosing character images 54
13.2.3 Formatting indicator 54
13.3 Content imaging process for formatted processable content 54

14 Interactions between presentation attributes and control functions 55

15 Definition of character content architecture classes 55
15.1 Formatted character content architecture class 56
15.2 Processable character content architecture class 56
15.3 Formatted processable character content architecture class 56

Annexes

A Summary of content architecture classes 59
A.1 Formatted character content architecture classes 59
A.2 Processable character content architecture classes 62
A.3 Formatted processable character content architecture classes 64

B Character content architecture levels 67
B.1 Character content architecture level CF–0 68
B.2 Character content architecture level CF–1 68
B.3 Character content architecture level CF–2 70
B.4 Character content architecture level CF–3 71
B.5 Character content architecture level CP–0 74
B.6 Character content architecture level CP–2 75
B.7 Character content architecture level CP–3 77
B.8 Character content architecture level CFP–2 80
B.9 Character content architecture level CFP–3 82

C Coded representations of control functions 86

D Summary of object identifiers 87

E SGML representation of character content–specific attributes for ODL 88
E.1 Introduction 88
E.2 Names and public identifiers 88
E.3 Representation of attribute values 88
E.4 Presentation attributes 90
E.5 Coding attributes 91